



# **EXHIBIT 11**

## **(part 3)**

A zero turning mower with zero deficiencies.

## model 202

For those requiring a dedicated mowing machine, the Stenier 202 combines a zero turning radius with our passion for zero defects. Not only does it mow rings around other mowers, the Stenier 202 floats over uneven terrain with a unique mower deck that flexes as it gives for an even, clean cut. And no mower is easier to operate. Twin hydrostatic controls provide a steady ride, smooth power and easy handling — with minimal training — while a single park lever and cutting height handle allow for fast, easy adjustments. (Mulching adapter kit available.)





## Accessories

Accommodates and comfort, safety

For added comfort, safety and utility, choose from optional accessories that provide Steiner quality with a custom design and fit. For more information about these and other accessories for your turf tractor, contact your authorized Steiner dealer.



**Industry Moves**  
Light Coasting, 3-blade rotors recover  
structure tapered rotors by using a double  
assembly. Cutting height is  
controlled by the front rotors which  
and is 8 ft high over water. First  
encountered device gives constant  
inability for maintenance and  
decrease. High capacity discharge  
boxes provide even distribution of  
system.



[illegible][illegible]

This power because a molding  
money is a few dollars more  
with the installation of the proper  
made and built system.


Over 2000 ..... 22.50  
Coping work ..... 50  
Coping work ..... 100  
Coping work ..... 150  
Coping work ..... 200  
Coping work ..... 250  
Coping work ..... 300  
Coping work ..... 350  
Coping work ..... 400  
Coping work ..... 450  
Coping work ..... 500  
Coping work ..... 550  
Coping work ..... 600  
Coping work ..... 650  
Coping work ..... 700  
Coping work ..... 750  
Coping work ..... 800  
Coping work ..... 850  
Coping work ..... 900  
Coping work ..... 950  
Coping work ..... 1000



**Two Extra Miles**  
The tire factor power is designed for the Model A's 1600 and 4100 tractors. Our tread depth provides good stability for two-axle tractors. Single front axles where it needs the extra height of the two-axle blades.



**My Boss**  
A quick, easy way to make loose  
hundreds or thousands of dollars.  
In fact, you can see it for virtually  
anything that would normally  
require a water barrier.



## Attachments

www.1911forum.com

at 125.

Veracity is as much a part of the Steiner story as superior

engineering or long-term reliability. Using our Quick

**Which™ attachments, your**


almost any turf or grounds maintenance task within one

to five minutes. Discover why so many Steiner owners like

of their turf tractors as true  
all purpose machines.

4-1000000	5-200000	6-300000	7-400000	8-500000	9-600000	10-700000	11-800000	12-900000	13-1000000	14-1100000	15-1200000	16-1300000	17-1400000	18-1500000	19-1600000	20-1700000	21-1800000	22-1900000	23-2000000	24-2100000	25-2200000	26-2300000	27-2400000	28-2500000	29-2600000	30-2700000	31-2800000	32-2900000	33-3000000	34-3100000	35-3200000	36-3300000	37-3400000	38-3500000	39-3600000	40-3700000	41-3800000	42-3900000	43-4000000	44-4100000	45-4200000	46-4300000	47-4400000	48-4500000	49-4600000	50-4700000	51-4800000	52-4900000	53-5000000	54-5100000	55-5200000	56-5300000	57-5400000	58-5500000	59-5600000	60-5700000	61-5800000	62-5900000	63-6000000	64-6100000	65-6200000	66-6300000	67-6400000	68-6500000	69-6600000	70-6700000	71-6800000	72-6900000	73-7000000	74-7100000	75-7200000	76-7300000	77-7400000	78-7500000	79-7600000	80-7700000	81-7800000	82-7900000	83-8000000	84-8100000	85-8200000	86-8300000	87-8400000	88-8500000	89-8600000	90-8700000	91-8800000	92-8900000	93-9000000	94-9100000	95-9200000	96-9300000	97-9400000	98-9500000	99-9600000	100-9700000	101-9800000	102-9900000	103-10000000																																																																															
Arctic 1/2 in	Arctic 3/4 in	Arctic 1 in	Arctic 1 1/2 in	Arctic 2 in	Arctic 2 1/2 in	Arctic 3 in	Arctic 3 1/2 in	Arctic 4 in	Arctic 4 1/2 in	Arctic 5 in	Arctic 5 1/2 in	Arctic 6 in	Arctic 6 1/2 in	Arctic 7 in	Arctic 7 1/2 in	Arctic 8 in	Arctic 8 1/2 in	Arctic 9 in	Arctic 9 1/2 in	Arctic 10 in	Arctic 10 1/2 in	Arctic 11 in	Arctic 11 1/2 in	Arctic 12 in	Arctic 12 1/2 in	Arctic 13 in	Arctic 13 1/2 in	Arctic 14 in	Arctic 14 1/2 in	Arctic 15 in	Arctic 15 1/2 in	Arctic 16 in	Arctic 16 1/2 in	Arctic 17 in	Arctic 17 1/2 in	Arctic 18 in	Arctic 18 1/2 in	Arctic 19 in	Arctic 19 1/2 in	Arctic 20 in	Arctic 20 1/2 in	Arctic 21 in	Arctic 21 1/2 in	Arctic 22 in	Arctic 22 1/2 in	Arctic 23 in	Arctic 23 1/2 in	Arctic 24 in	Arctic 24 1/2 in	Arctic 25 in	Arctic 25 1/2 in	Arctic 26 in	Arctic 26 1/2 in	Arctic 27 in	Arctic 27 1/2 in	Arctic 28 in	Arctic 28 1/2 in	Arctic 29 in	Arctic 29 1/2 in	Arctic 30 in	Arctic 30 1/2 in	Arctic 31 in	Arctic 31 1/2 in	Arctic 32 in	Arctic 32 1/2 in	Arctic 33 in	Arctic 33 1/2 in	Arctic 34 in	Arctic 34 1/2 in	Arctic 35 in	Arctic 35 1/2 in	Arctic 36 in	Arctic 36 1/2 in	Arctic 37 in	Arctic 37 1/2 in	Arctic 38 in	Arctic 38 1/2 in	Arctic 39 in	Arctic 39 1/2 in	Arctic 40 in	Arctic 40 1/2 in	Arctic 41 in	Arctic 41 1/2 in	Arctic 42 in	Arctic 42 1/2 in	Arctic 43 in	Arctic 43 1/2 in	Arctic 44 in	Arctic 44 1/2 in	Arctic 45 in	Arctic 45 1/2 in	Arctic 46 in	Arctic 46 1/2 in	Arctic 47 in	Arctic 47 1/2 in	Arctic 48 in	Arctic 48 1/2 in	Arctic 49 in	Arctic 49 1/2 in	Arctic 50 in	Arctic 50 1/2 in	Arctic 51 in	Arctic 51 1/2 in	Arctic 52 in	Arctic 52 1/2 in	Arctic 53 in	Arctic 53 1/2 in	Arctic 54 in	Arctic 54 1/2 in	Arctic 55 in	Arctic 55 1/2 in	Arctic 56 in	Arctic 56 1/2 in	Arctic 57 in	Arctic 57 1/2 in	Arctic 58 in	Arctic 58 1/2 in	Arctic 59 in	Arctic 59 1/2 in	Arctic 60 in	Arctic 60 1/2 in	Arctic 61 in	Arctic 61 1/2 in	Arctic 62 in	Arctic 62 1/2 in	Arctic 63 in	Arctic 63 1/2 in	Arctic 64 in	Arctic 64 1/2 in	Arctic 65 in	Arctic 65 1/2 in	Arctic 66 in	Arctic 66 1/2 in	Arctic 67 in	Arctic 67 1/2 in	Arctic 68 in	Arctic 68 1/2 in	Arctic 69 in	Arctic 69 1/2 in	Arctic 70 in	Arctic 70 1/2 in	Arctic 71 in	Arctic 71 1/2 in	Arctic 72 in	Arctic 72 1/2 in	Arctic 73 in	Arctic 73 1/2 in	Arctic 74 in	Arctic 74 1/2 in	Arctic 75 in	Arctic 75 1/2 in	Arctic 76 in	Arctic 76 1/2 in	Arctic 77 in	Arctic 77 1/2 in	Arctic 78 in	Arctic 78 1/2 in	Arctic 79 in	Arctic 79 1/2 in	Arctic 80 in	Arctic 80 1/2 in	Arctic 81 in	Arctic 81 1/2 in	Arctic 82 in	Arctic 82 1/2 in	Arctic 83 in	Arctic 83 1/2 in	Arctic 84 in	Arctic 84 1/2 in	Arctic 85 in	Arctic 85 1/2 in	Arctic 86 in	Arctic 86 1/2 in	Arctic 87 in	Arctic 87 1/2 in	Arctic 88 in	Arctic 88 1/2 in	Arctic 89

NAME: \_\_\_\_\_



At present, the situation is not as bleak as it once was. The number of people who are unemployed has fallen from 15 million in 1982 to 12 million in 1987. The number of people who are underemployed has fallen from 10 million in 1982 to 7 million in 1987. The number of people who are overemployed has fallen from 5 million in 1982 to 3 million in 1987. The number of people who are underemployed and overemployed has fallen from 5 million in 1982 to 3 million in 1987. The number of people who are underemployed and overemployed has fallen from 5 million in 1982 to 3 million in 1987.

[illegible][illegible]

**Power Plants**  
350 mph blinding power easily clears  
hazes and dirties. Also bling haze  
even hooding areas with black-  
out has on blacked lower fan and  
vertical ductwork close. Also  
some areas are not able to be

[illegible]

**Blue Whirl**  
The loom never stops and the  
energy is such as to clean, back,  
change colors, and alter hand to reach  
the customer's requirements.

Overall width	115"
Art. content	50%
Overall depth	50"
Lead or height	27"
Weight	175 lbs. net crane and 775 lbs. crane
775 lbs. crane	175 lbs. net crane and 775 lbs. crane
Angle of movement	32° above horizontal
Weight of load	25 lbs.
Weight of unit	175 lbs.
Power source	115V 60 Hz 150°
Motor	1/2 hp
Washer	1/2 hp
Weight	225 lbs.
Control	115V 60 Hz
Control	115V 60 Hz



**WATERBURY**



re details  
a, parting  
hydrocal  
in bridge  
cable.




about 1  
million



NOTE: These considerations are subject to change without notice.

**JACOBSEN®**

# HR-5111™ 4WD Hydraulic Mower



## The Professional's Choice on Turf

## Specifications

[illegible]

116. *See also the references. Significant improvement for all items measured. Significant declines*

**STEINER**

Steiner Turf Equipment, Inc.  
289 N. Kirtzen Rd.  
P.O. Box 504  
Dalton, OH 44618-0504  
330-835-0300  
Fax 330-823-1003

## HR-5111: The All-Hydraulic

The HR-5111 delivers a productive 31-foot cut to rough, muck, and other large turf areas. Its three All-Hydraulic moving decks, four-wheel-drive (4WD) traction, and a comfortable operator station, make the HR-5111 the right mower for your big job.

**All-Hydraulic, High-Production Mowing**  
The HR-5111's revolutionary All-Hydraulic mowing decks deliver the highest quality cut or high-production mow with less fuel consumption and less wear on the mowing deck.

The floating deck design, with large castor wheels and self-aligning rollers, follows turf contours and reduces the risk of scalping. Cutting heights are adjustable from 1 to 5 1/2 inches. Spring wipers on side deck mounting arms absorb impact. Mow with one, two, or all three decks, to match conditions.

The HR-5111's rigid, compact design with hydrostatic transmission and rear-wheel power steering allows close turns around trees in open areas. The HR-5111 cuts up to 65 acres per day.



**No Bells, No Bells**  
Individual hydraulic control for each of the HR-5111's blades for a quality cut without the bells of bells, pulleys, lifters, deck lift, or other mechanical parts. Opposite directions for even discharging.

### 4-Wheel Drive Traction

Hydraulic 4WD with differential lock, tackles tough hills that stall the competition. A hydraulic weight transfer system shifts the weight of the deck to the vehicle's full drive wheels. Unlike mechanical 4WD, the HR-5111's 4WD system can be engaged or disengaged at any time, to prevent turf scuffing and provide full traction.

**Built For Trouble-Free Operation**  
The HR-5111's 31-foot cut is made possible by the All-Hydraulic decks. Each motor has self-lubricating spindles for less maintenance.

The wing decks tilt vertically when raised, and the front deck tilts vertically by removing two pins at the rear of the

deck, for easy cleaning and servicing. Diagnostic ports make it easy to check hydraulic pressure.

**Economical Diesel Power**  
The HR-5111 is powered by a reliable, efficient 51-horsepower, four-cylinder, liquid-cooled diesel engine. The engine is fully protected by a hood and isolation mounted for cleaner, quieter operation. A top-mounted, heavy-duty air cleaner protects the engine from harmful dirt and chipping.


The hood lifts up and back for full access to the engine. The hydraulic oil cooler slides away from the radiator for cleaning. The HR-5111's durable fiberglass body keeps its good looks, even in harsh conditions.

• Adjustable seat, center console, and steering wheel for operator comfort.

• Hydraulic 4WD for sure traction without turf damage.

• Floating decks, casters, and self-aligning rollers for superior quality cut.

• All hydraulic decks, speed less maintenance, have smoother discharge.



• Ergonomic design puts controls, instruments in easy reach, sight.

• Rear-wheel power steering, center console, 4WD lever for close maneuvering.

## 4WD High Production Rotary

The box chum steel frame and heavy-duty axle can handle years of mowing. And it's backed by a two-year/1500-hour warranty.

**Built For Operator Comfort**  
Your operators will like the HR-5111's comfortable high-back seat, center console and full steering wheel. Good visibility without blind spots. A full array of gauges and warning lights keep operators aware of vital mower functions. For extra protection, a horn sounds if engine coolant or hydraulic oil begins to overheat.


A ROTs and seat belt are standard on the HR-5111. A canopy with lights and flashers, or a factory-installed cab with windshield wiper and heater are also available.

• Diagnostic ports to check hydraulic pressure.

• Fiberglass body keeps its good looks longer.

• ROTs, seat belt, standard canopy with light, or factory-installed cab with windshield wiper and heater are available.

• Fuel efficient, powerful 51-hp diesel engine.




The HR-5111 features dynamic braking, along with heavy-duty hydraulic disc brakes on the drive wheels for sure stopping.

For year-round versatility, a 42-inch snow thrower and 72-inch rotary brush are also available.

For quality, high-production mowing, versatility, and operator comfort, in a reliable package, call your Jacobson dealer today for a demonstration of the HR-5111.

\*Circle numbers on Reader Service card for more information on jobs.

\*\*See your Jacobson dealer for complete warranty details.




Adjustable suspension seat, full steering wheel, center console, 4WD lever for close maneuvering, and diagnostic ports to check hydraulic pressure.











Find State OSHA regulations based on:

\* Specifications and design subject to change without notice.

PRODUCTS MASTER SPEC 380-D Page

Home | About Us | Job Openings | Contact Us | Current Products |  
 New Products | Backhoe Loaders | Excavators | Graders | Motor Graders | Roll-Over Protection |  
 Pavers | Compactors | Dozers | Scrapers | Motor Graders | Motor Graders | Motor Graders | Motor Graders |  
 Copyright © 2000 The Toro Company. All rights reserved. Toro is a registered trademark of Toro Company.

11/10/00

<http://www.toro.com/products/groundsmaster/specs/spec380-d.html>


12/28/2000

[illegible]

**The Articulator®**  
Model 325ER

**aslec®**

"Quality Rotary Movers For A World That Isn't Flat!"




## Introducing the Model 325ER Articulator

A PTO Driven 72" Articulating Grooming Mower  
That Thinks It's Three 25" Push Mowers.

The world's finest self-cleaning cut with Articulators because they can afford the best. Now the best has become more affordable. The Model 325ER is a three-deck version of the 25" Articulator that cut the extreme length of the best championship courses. No skipping. No missed grass. That's the Articulator trademark. A trademark of perfectly grooming the most extreme green surrounds, elevated tee beds, bunkers, or even the contours of your back yard.

Side discharge and mulching capabilities make the Model 325ER safe and versatile for any finish mowing applications. Coupled with a small utility tractor, it surpasses the productivity and quality of self-propelled mowers in a fraction of their cost. The rear mounted location and high lift blades even eliminate tractor wheel marks. The Articulator. The best quality. The best value. The best return.

GCSAA SHOW 1997  
LAS VEGAS




The Model 325ER Articulator can be powered and transported by small utility tractors with under 20 HP.

### The Model 325ER Articulator General Specifications

Overall Cutting Width	72"
Cutting Deck Diameter	31 1/2"
Cutting Height Range	1" to 4"
Cutting Deck Pivotal Material	316 Stainless Steel
Top Deck Capacity (lb.)	11,000 (11000) Capacity (lb.) 11,000
Top Deck Capacity (lb.)	11,000 (11000) Capacity (lb.) 11,000
PTO Shaft Horsepower (hp)	17,000 (17000) PTO Shaft Horsepower (hp) 17,000
Blade Type	3" x 12" x 1/2" Heavy High Lift, Hardened Steel
Blade Width	30" (3000) Blade Width (inches) 30"
Blade Spacing	5" (5000) Blade Spacing (inches) 5"
Blade Material	316 Stainless Steel (316) Blade Material (inches) 316
Weight (lb.)	1140 (11400) Weight (lb.) 1140

Features include: 27 Revolutions Per Minute (RPM) Blade Speed  
PTO Shaft Horsepower (hp) 17,000 (17000) PTO Shaft Horsepower (hp) 17,000

Articulator



## In 1492 Columbus Discovered That The World Wasn't Flat

## Over Five Centuries Later

## Lastec Did Something About It

Lastec builds quality mowers for a world that isn't flat. That's why our 325E floats three 25" decks to cut a 72" path and why it's wide and low to the ground. We believe contoured ground should be cut, not scalped. The best turf professionals in the world agree. That's why every active player in the PGA has played on grass cut by an Articulator. Discover the difference. Discover Lastec.

Use any of three control positions





**If Mowing Grass Was A Race**  
**This Is The Only View Our Competitors Would Ever Have**



72" Cutting Width  
 17 to 4" Cutting Heights  
 Three 25" Articulating Decks  
 Complete Set of Working Controls  
 Dual Hand & Foot Riding Controls  
 Hydraulic Drive with Dual Oil Cooler  
 22 HP Kohler Command Engine  
 Power Folding Deck Drive System  
 Steering with Hazard Flashers  
 Front-Final Deck Gauge Wheels  
 Dual 5 Gallon Fuel Tanks

Luster has been building mowers for the high-end golf industry since 1992. All Luster equipment is sold and serviced through a select group of our dealers around the world. If you would like to find out more about the entire Luster line of turf equipment, call the factory for the dealer nearest you.

Manufactured by Luster Inc., 7865 N CR 100E Ligon, IN 46149 Voice (317) 892-4444 Fax (317) 892-4188  
 Patents Pending. All Specifications subject to change without notice. Printed in the USA

**as/eco**

**UNITED STATES DEPARTMENT OF COMMERCE**  
**Patent and Trademark Office**  
 COMMISSIONER OF PATENTS AND TRADEMARKS  
 Address: Washington, D.C. 20231

**APPLICATION NO.** 09/646,145 **PRIOR DATE** 04/10/00 **INVENTOR** BEDHAR **ATTORNEY DOCKET NO.** 7016R-000015

**EXAMINER** R 7016R-000015

**CLASSIFICATION** PM82/0227

**PAPER NUMBER** PM82/0227

**DATE** 02/27/01

**Commissioner of Patents and Trademarks**

Please find below and/or attached an Office communication concerning this application or proceeding.

PTO/DOC (Form 600) 1-10-00



Page 2

Application/Control Number: 09/546,145

Art Unit: 3671

## DETAILED ACTION

## Double Patenting

1. The nonstatutory double patenting rejection is based on a judicially created doctrine grounded in public policy (a policy reflected in the statute) so as to prevent the unjustified or improper timewise extension of the "right to exclude" granted by a patent and to prevent possible harassment by multiple assignees. See *In re Goodman*, 11 F.3d 1046, 29 USPQ2d 2010 (Fed. Cir. 1993); *In re Long*, 759 F.2d 887, 225 USPQ 645 (Fed. Cir. 1985); *In re Van Orman*, 686 F.2d 937, 214 USPQ 761 (CCPA 1982); *In re Vogel*, 422 F.2d 438, 164 USPQ 619 (CCPA 1970); and *In re Thoenigson*, 418 F.2d 522, 163 USPQ 644 (CCPA 1969).

A timely filed terminal disclaimer in compliance with 37 CFR 1.321(d) may be used to overcome an actual or provisional rejection based on a nonstatutory double patenting ground provided the conflicting application or patent is shown to be commonly owned with this application. See 37 CFR 1.321(b).

Effective January 1, 1994, a registered attorney or agent of record may sign a terminal disclaimer. A terminal disclaimer signed by the assignee must fully comply with 37 CFR 3.73(b).

2. Claims 1 and 21-31 are rejected under the judicially created doctrine of obviousness-type double patenting as being unpatentable over claims 1-19 of U.S. Patent No. 6,047,530. Although the conflicting claims are not identical, they are not patentably distinct from each other because both the patent and the instant application read themselves to a gang-type mower having a plurality of deck assemblies with a roller supporting and extending substantially the width of the decks.

Office Action Summary		Application No. 09/546,145	Examiner Robert Puzos	Art Unit 3671	Part of Paper No. 2
-----------------------	--	-------------------------------	--------------------------	------------------	---------------------

☐ Responsive to communication(s) filed on \_\_\_\_\_

☐ This action is FINAL.

☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1835 C.D. 11; 453 O.G. 213.

A shortened statutory period for response to this action is set to expire 2 months, or thirty days, whichever is longer, from the mailing date of this communication. Failure to respond within the period for response will cause the application to become abandoned. (35 U.S.C. § 133). Extensions of time may be obtained under the provisions of 37 CFR 1.136(d).

Disposition of Claims

☒ Claim(s) 1 and 21-31 ☐ are pending in the application.

☐ Of the above, claim(s) \_\_\_\_\_ ☐ are withdrawn from consideration.

☐ Claim(s) \_\_\_\_\_ ☐ are allowed.

☒ Claim(s) 1 and 21-31 ☐ are rejected.

☐ Claim(s) \_\_\_\_\_ ☐ are objected to.

☐ Claims \_\_\_\_\_ ☐ are subject to restriction or election requirement.

Application Papers

☐ See the attached Notice of Draftsperson's Patent Drawing Review, PTO-940.

☐ The drawing(s) filed on \_\_\_\_\_ ☐ are objected to by the Examiner.

☐ The proposed drawing correction, filed on \_\_\_\_\_, is ☐ Approved ☐ Disapproved.

☐ The specification is objected to by the Examiner.

☐ The oath or declaration is objected to by the Examiner.

Priority under 35 U.S.C. § 119

☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d).

☐ All ☐ Some ☐ None of the CERTIFIED copies of the priority document have been ☐ received.

☐ received in Application No. (Serial Code/Class) Number \_\_\_\_\_

☐ received in this national stage application from the International Bureau (PCT Rule 17.2(e)).

\* Certified copies not received:

☐ Acknowledgment is made of a claim for domestic priority under 35 U.S.C. § 110(e).

Attachments

☐ Notice of References Cited, PTO-892

☒ Information Disclosure Statement(s), PTO-1449, Paper No(s) 6

☐ Interview Summary, PTO-413

☐ Notice of Draftsperson's Patent Drawing Review, PTO-940

☐ Notice of Informal Patent Application, PTO-152

— SEE OFFICE ACTION ON THE FOLLOWING PAGES —

U.S. Patent and Trademark Office  
PTO-320 (Rev. 5-95)